









BETTER HOME PRODUCTS

LOW - PROFILE DEADBOLT SPECIFICATIONS

Skyline Blvd Collection 		BHP ITEM# SK10611DB Dark Bronze SK10615SN Satin Nickel SK10644BLK Matte Black SK10688CH Chrome SK10604SB Satin Brass Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4" Door Thickness - 1 3/8" to 1 3/4" Function: Locked or unlocked by key out side or turn-piece inside. inside always free Cylinder - 5 pin KW1 keyway. Other options available Strike - Packed with 1 Pc 1x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available
Skyline Blvd Collection 		BHP ITEM# SK10888CH Chrome SK10815SN Satin Nickel SK10811DB Dark Bronze SK10844BLK Matte Black Door Prep - One side bore 2 1/8" dia", Edge Bore 1". Door Thickness - 1 3/8" to 1 3/4" Function: Locked or unlocked by turn-piece inside. Strike - Packed with 1 Pc 1x2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available
Tiburon Collection 		BHP ITEM# TIB10611DB Dark Bronze TIB10615SN Satin Nickel TIB10644BLK Matte Black TIB10688CH Chrome TIB10604SB Satin Brass Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4" Door Thickness - 1 3/8" to 1 3/4" Function: Locked or unlocked by key out side or turn-piece inside. inside always free Cylinder - 5 pin KW1 keyway. Other options available Strike - Packed with 1 Pc 1x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available
Tiburon Collection 		BHP ITEM# TIB10888CH Chrome TIB10815SN Satin Nickel TIB10811DB Dark Bronze TIB10844BLK Matte Black Door Prep - One side bore 2 1/8", Edge Bore 1" Door Thickness - 1 3/8" to 1 3/4" Function: Locked or unlocked by turn-piece inside. Strike - Packed with 1 Pc 1x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available